

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

57758 SprayBond 500 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesive

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	OASE GmbH	
Street:	Tecklenburger Straße 161	
Place:	D-48477 Hörstel	
Telephone:	+49 (5454) 800	Telefax: +49 (5454) 8090
e-mail:	info@oase-livingwater.com	
Contact person:	Markus Dreyer; Forschung und Entwicklung	Telephone: +49 (5454) 80450
e-mail:	m.dreyer@oase-livingwater.com	
Internet:	www.oase-livingwater.com	
Responsible Department:	Dr. Gans-Eichler Chemieberatung GmbH Raesfeldstr. 22 D-48149 Münster	e-mail: info@tge-consult.de Tel.: +49 (0)251/924520-60 www.tge-consult.de

1.4. Emergency telephone number:

Beratungsstelle für Vergiftungserscheinung in Berlin: +49 (30) - 30686 790

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

acetone; propan-2-one; propanone

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 2 of 13

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Containers should be completely drained; Residues may cause an explosion hazard. Vapours are heavier than air and will spread at floor level.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
68476-85-7	Petroleum gases, liquefied; Petroleum gas	30-60 %
	270-704-2	
	Flam. Gas 1, Liquefied gas; H220 H280	
67-64-1	acetone; propan-2-one; propanone	10-30 %
	200-662-2	606-001-00-8
	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane	10-30 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH).

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 3 of 13

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist. Never loosen glued eyelids with force.

After ingestion

If swallowed, immediately drink: Water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Nausea. headache, dizziness, drowsiness. Coughing. difficulties of breathing.

Following inhalation: Coughing. Dizziness. at high concentration: unconsciousness.

After skin contact: Symptoms: reddening, irritation. Drying-out effect resulting in rough and chapped skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Carbon dioxide. Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO₂). Carbon monoxide Gas/vapours, irritant.

Explosion risk in contact with: heat, flames and sparks. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear protective gloves/protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Eliminate leaks immediately. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 4 of 13

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.
Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.
Provide adequate ventilation.

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.
Oxidizing liquids. Oxidizing solids. Self-reactive substances and mixtures. Organic peroxides. Radioactive substances.

Infectious substances.

Further information on storage conditions

Recommended storage temperature: 10-30°C. Do not store at temperatures over: 50°C

Note: Storage requirements for flammable aerosols TRG 300

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
68476-85-7	Liquefied petroleum gas	1000	1750		TWA (8 h)	WEL
		1250	2180		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	2420 mg/m ³
Worker DNEL, long-term		inhalation	systemic	1210 mg/m ³
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m ³
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2 035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

PNEC values

CAS No	Substance	Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Freshwater (intermittent releases)		21 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Always close containers tightly after the removal of product.

When using do not eat, drink, smoke, sniff.

Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (DIN EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 6 of 13

Butyl rubber. (0,5 mm)
 Breakthrough time >480 min
 penetration time (maximum wearing period): >160 min
 The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.
 Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing.
 Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.
 Respiratory protection necessary at:
 exceeding exposure limit values
 Insufficient ventilation.
 Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).
 Use only respiratory protection equipment with CE-symbol including four digit test number.
 During spraying, use a mask with the following filter cartridge: Type AX gas filter.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	amber	
Odour:	characteristic	
pH-Value:		7

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Sublimation point:	not determined
Softening point:	not determined
Flash point:	not determined

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits:	not determined
Upper explosion limits:	not determined

Oxidizing properties

none

Vapour pressure:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,84 g/cm ³

Solubility in other solvents

not determined

Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 7 of 13

Flow time:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapors form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat.
Ignition hazard.
Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Strong acid. Oxidizing agents, strong. Strong acid.

10.6. Hazardous decomposition productsIn use, may form flammable/explosive vapour-air mixture. Can be released in case of fire: Carbon dioxide (CO₂). Carbon monoxide**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68476-85-7	Petroleum gases, liquefied; Petroleum gas				
	inhalative (4 h) vapour	LC50 >20 mg/l	Rat.	(M)SDS external	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalative (4 h) vapour	LC50 50,1 mg/l	Rat	RTECS	
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane				
	oral	LD50 >2000 (read across) mg/kg	Rat.	ECHA Dossier	
	dermal	LD50 >2000 (read across) mg/kg	Rabbit	ECHA Dossier	
	inhalative (4 h) vapour	LC50 > 25,2 mg/l	Rat. OECD 403	ECHA Dossier	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Acetone:

Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents);

Species: Mouse.; Exposure duration: 90d; Result: NOAEL = 4858 mg/kg ; Literature information: ECHA

Dossier; In-vitro mutagenicity: Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test);

Result: negative. Literature information: ECHA Dossier; No indications of human carcinogenicity exist.

Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414

(Prenatal Developmental Toxicity Study) ; Species: Rat; Exposure duration: 14d; Result: NOAEL = 11000 ppm;

Literature information: ECHA Dossier

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone; Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Acetone:

Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents);

Species: Mouse.; Exposure duration: 90d; Result: NOAEL = 4858 mg/kg ; Literature information: ECHA

Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68476-85-7	Petroleum gases, liquefied; Petroleum gas					
	Acute fish toxicity	LC50 >10 < 200 mg/l	96 h	QSAR Calculations	ECHA dossier	
	Acute algae toxicity	ErC50 >1 < 100 mg/l		QSAR Calculations	ECHA dossier	
	Acute crustacea toxicity	EC50 >10 <100 mg/l	48 h	QSAR Calculations	ECHA dossier	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 5540 mg/l	96 h	Onchorhynchus mykiss	ECHA Dossier	
	Acute crustacea toxicity	EC50 8800 mg/l	48 h	Daphnia pulex	ECHA Dossier	
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 11,4 mg/l	96 h	Onchorhynchus mykiss	OECD 203	
	Acute algae toxicity	ErC50 30 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna	OECD 202	

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68476-85-7	Petroleum gases, liquefied; Petroleum gas			
	Non-GLP non-guideline experimental study	100%	26	ECHA Dossier
67-64-1	acetone; propan-2-one; propanone			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	90%	28	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane			
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	98%	28	ECHA dossier
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68476-85-7	Petroleum gases, liquefied; Petroleum gas	2,3
67-64-1	acetone; propan-2-one; propanone	-0,24
	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane	2,89

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 10 of 13

Advice on disposal

Dispose of waste according to applicable legislation.
 Non-contaminated packages may be recycled.
 According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.
 Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 11 of 13

Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 29: Petroleum gases, liquefied; Petroleum gas

2010/75/EU (VOC): not determined
 2004/42/EC (VOC): 544 g/l
 Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Aerosol directive (75/324/EEC)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 12 of 13

REACH 1907/2006 Appendix XVII: 3, 29

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

acetone; propan-2-one; propanone

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclics, <5% n-hexane

SECTION 16: Other information

Changes

Rev. 1.00; Initial release: 19.10.2017

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern

TRGS Technische Regeln fuerGefahrstoffe

TSCA: Toxic Substances Control Act

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

Safety Data Sheet

according to Regulation (EC) No 1907/2006

57758 SprayBond 500 ml

Revision date: 19.10.2017

Product code:

Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)